

MonoDome Camera D22



Fits In. Watches Out.

Inconspicuous surveillance with state-of-the-art technology. The D22 FixDome from MOBOTIX adapts perfectly to any task. Exchangeable lenses, various mounting and configuration options including vandalism set support unlimited application possibilities.



MOBOTIX HiRes video replaces up to 6 cameras ...

- Attractively designed FixDome camera featuring exchangeable lenses from Tele to Wide Angle
- Numerous installation options both indoor and outdoor
- On-wall set with space for extension modules (battery, UMTS, WLAN, etc.)
- Integrated DVR with HiRes video recording
- Robust, low-maintenance and weatherproof from -30° to $+60^{\circ}\text{C}$ (-22° to $+140^{\circ}\text{F}$), (IP65)
- Digital continuous zoom, pan and tilt
- Can be upgraded to an intercom system with the MOBOTIX ExtIO module

D22 - Compact, Cost-Efficient And With High Resolution

The many, easy-to-replace lens options of the D22 provide a tailored solution for different types of applications. A robust dome camera (IP65) with optional vandal-proof, wall-mount and in-ceiling installation sets.

Technical Specifications D22



The HiRes Video Company **MOBOTIX**

Technical Specifications D22 MonoDome	
Models	Basic, IT, IT-Night, Sec, Sec-Night
Lenses	22 to 135 mm format, horizontal angle 90° to 15°
Sensitivity	Color: 1 lux (t=1/60 s), 0,05 lux (t=1/1 s) B/W: 0,1 lux (t=1/60 s), 0,005 lux (t=1/1 s)
Sensor	1/2" CMOS, progressive scan
Max. image resolution	Color: 2048 x 1536 (3Mega), B/W: 1280 x 960 (Mega)
Image format	2048 x 1536, 1280 x 960, 1024 x 768, 800 x 600, 768 x 576 (D1), 704 x 576 (TV-PAL), 640 x 480, 384 x 288, 352 x 288, 320 x 240, 160 x 120; free image format selection (e.g. 1000 x 200 for skyline)
Max frame rate (M-JPEG) (Live/Recording)	VGA: 16 fps, TV-PAL: 12 fps, Mega: 6 fps, 3Mega: 4 fps
Video stream (MxPEG) (Live/Recording/Audio)	VGA: 30 fps, TV-PAL: 24 fps, Mega: 14 fps, 3Mega: 10 fps
Image compression	MxPEG, M-JPEG, JPG, H.263 (Video-VoIP-Telephony)
Internal DVR	Slot for SD card (up to 16 GB)
External storage	Directly on NAS and PC/Server without additional recording software
Software (inclusive)	Video management software MxEasy, Control room software MxControlCenter
Image processing	Backlight compensation, automatic white balance, image distortion correction, video sensor (motion detection)
Virtual PTZ	Digital Pan/Tilt/Zoom, continuous 8x zoom
Alarm/Events	Triggering of events by integrated multiple-window motion detection, external signal, temperature sensor, notification over email, FTP, IP-Telephony (VoIP, SIP), visual/acoustic alarm, Pre- and post-alarm images
Audio	Optional via ExtIO, video VoIP supported
Interfaces	Ethernet 10/100, USB, Audio (microphone/speaker)
Video/Telephony	VoIP, SIP, two-way speaker, remote controlling of the camera in- and outputs, event notification
Security	User-/Group management, HTTPS/SSL, IP address filter, IEEE 802.1x, Intrusion Detection
Certificates	BGV C 9; EMC: DIN EN 61000, DIN EN 50155 (shock, vibration, temperature), FCC part 15B; CE
Power supply	Year-round Power over Ethernet (IEEE 802.3af, Class 0), Netpower-Adapter, typ. 2,5 W
Operating conditions	IP65 (DIN EN 60529), -30° to +60 °C (-22°F to +140°F)
Dimensions	Ø x H: 16 x 8,6 cm, Weight: ca. 350 g
Standard delivery	Housing (high-resistance composites - PBT-PC), white, shockproof polycarbonate dome (transparent), free choice of lenses, mounting parts, allen wrench, patch cable, manual, software

Technical information subject to change without notice!

Available Accessories D22 MonoDome					
In-Ceiling Set MX-D22M-OPT-IC  <ul style="list-style-type: none"> Consists of in-ceiling mount and mounting parts Easy mounting from front Ø 150 mm installation dimension It can be ordered with stainless steel cover 	On-Wall Set MX-D22M-OPT-AP  <ul style="list-style-type: none"> Consists of On-Wall mount and mounting parts Protects the cabling 165 mm x 37 mm 	Vandalism Set MX-D22M-Vandal-Kit  <ul style="list-style-type: none"> Reinforced dome (3 mm Polyc.) Stainless steel vandalism housing polished or matt, in white, silvergray or black 	Outdoor Wall Mount MX-D22M-OPT-WH  <ul style="list-style-type: none"> Weatherproof (IP65) Covers RJ45 wall outlets Space for expansion modules (WLAN) 	Pole Mount MX-D22M-OPT-MH  <ul style="list-style-type: none"> 3 mm stainless steel, white 2 stainless steel straps for pole diameter 60-180 mm, incl. mounting parts 	ExtIO Extension Module MX-ExtIO  <ul style="list-style-type: none"> Microphone/speaker PIR sensor for motion detection, temperature sensor Integrated switch functions

	L22 Super Wide Angle 90°	L32 Wide Angle 60°	L43 Wide Angle 45°	L65 Tele 31°	L135 Tele 15°
Lenses					
	approx. 90°H x 67°V at 10 m appr: 20.0 x 13.3 m	approx. 60°H x 45°V at 10 m appr: 11.5 x 8.2 m	approx. 45°H x 34°V at 10 m appr: 8.2 x 6.1 m	approx. 31°H x 23°V at 10 m appr: 5.5 x 4.0 m	approx. 15°H x 11°V at 10 m appr: 2.6 x 1.9 m

D22 - Compact, Cost-Efficient And With High Resolution

The many, easy-to-replace lens options of the D22 provide a tailored solution for different types of applications. A robust dome camera (IP65) with optional vandal-proof, wall-mount and in-ceiling installation sets.